


閘箱尺寸  
DIMENSIONS OF ENCLOSURE BOX (L1 & L2)

SHUTTER WIDTH	L1 (mm)	L2 (mm)
10	1100	800
20	1450	1200
30	1550	1100
40	1750	1400

\* AN EVEN FLOOR LEVEL MUST BE PROVIDED THROUGHOUT TRAVEL OF THE SHUTTER 簾頁軌跡所經的地面要在同一水平線上

- |  |        |
|--|--------|
| 1. ENCLOSURE BOX                           | 閘箱     |
| 2. STEEL HANGER                            | 穩固件    |
| 3. TOP TRACK                               | 導軌     |
| 4. RECEIVING CHANNEL                       | 接收槽    |
| 5. PERFORATED SLAT                         | 針孔簾頁   |
| 6. PORTABLE BOTTOM TRACK                   | 可移動地軌  |
| 7. LEADING EDGE                            | 牽引件    |
| 8. FLOOR SOCKET W/SPRING RETURN DUST COVER | 地插連防塵蓋 |



CHUNG TAI  
ROLLER SHUTTERS CO. LTD.  
UNIT 7, G/F, KIN FAT INDUSTRIAL CENTRE,  
KIN FAT ST., TUEN MUN, N.T.  
TEL: +852 2465 9323  
FAX: +852 2456 1364  
E-mail: info@chungtai-rs.com.hk

DRAWING NO.: L-PR\_75F  
DRAWING TITLE:  
COMPONENTS OF STEEL PERFORATED SLATS (75F)  
CURTAIN MOTOR OPERATED LATERALLY SLIDING SHUTTER

針孔簾頁 (75F) 電動橫趟閘組件圖